

NEW!



SoloTech™ 10 Hose Pump

- Max flow: 2.5 lpm (0.67 gpm)
- 10 mm hose



SoloTech™ 23 Hose Pump

- Max flow: 17 lpm (4.5 gpm)
- 23 mm hose



SoloTech™ 26 Hose Pump

- Max flow: 37.1 lpm (9.8 gpm)
- 26 mm hose



SoloTech™ 30 Hose Pump

- Max flow: 59.8 lpm (15.8 gpm)
- 30 mm hose



Husky™ 1050e

- 1 in (25.4 mm) connection
- Max flow: 159 lpm (42 gpm)
- Aluminium, polypropylene, stainless steel



ChemSafe™ 205

- 1/4 in (6.3 mm) connection
- Max flow: 9.5 lpm (2.5 gpm)



ChemSafe™ 307

- 3/8 in (9.4 mm) connection
- Max flow: 25.4 lpm (6.7 gpm)



ChemSafe™ 515

- 1/2 in (12.7 mm) connection
- Max flow: 60.6 lpm (16 gpm)



ChemSafe™ 1040

- 1 in (25.4 mm) connection
- Max flow: 146 lpm (38.8 gpm)



ChemSafe™ 1590

- 1-1/2 in (38.1 mm) connection
- Max flow: 376 lpm (99.5 gpm)



Husky 205

- 1/4 in (6.3 mm) connection
- Max flow: 19 lpm (5 gpm)
- Polypropylene, acetal, PVDF



Husky 307

- 3/8 in (9.4 mm) connection
- Max flow: 26 lpm (7 gpm)
- Polypropylene, acetal



Husky 515

- 1/2 in (12.7 mm) connection
- Max flow: 57 lpm (15 gpm)
- Polypropylene, acetal, PVDF



Husky 716

- 3/4 in (19.1 mm) connection
- Max flow: 61 lpm (16 gpm)
- Aluminium, SST



Husky 1050

- 1 in (25.4 mm) connection
- Max flow: 189 lpm (50 gpm)
- Aluminium, polypropylene, conductive polypropylene, PVDF, SST, hastelloy



Husky 1050HP

- 1 in (25.4 mm) connection
- Max flow: 189 lpm (50 gpm)
- Aluminium and SST



Husky 1590

- 1-1/2 in (38.1 mm) connection
- Max flow: 340 lpm (90 gpm)
- Polypropylene, PVDF, aluminium, SST



Husky 15120

- 1-1/2 in (38.1 mm) connection
- Max flow: 454 lpm (120 gpm)
- Polypropylene, PVDF



Husky 2150

- 2 in (50.8 mm) connection
- Max flow: 568 lpm (150 gpm)
- Polypropylene, PVDF, aluminium, SST, iron



Husky 2200

- 2 in (50.8 mm) connection
- Max flow: 757 lpm (200 gpm)
- Polypropylene, PVDF



Husky 3300

- 3 in (76.2 mm) connection
- Max flow: 1135 lpm (300 gpm)
- Polypropylene, aluminium, SST



Husky Dispense System

- For 200 l (55 gallon) drums
- Full-width mixing provides color and material consistency throughout the drum



Husky 515 Transfer Pump

- 1/2 in (12.7 mm) connection
- Max flow: 45 lpm (12 gpm)
- Polypropylene, acetal, PVDF



Husky 716 Transfer Pump

- 3/4 in (19.1 mm) connection
- Max flow: 52 lpm (14 gpm)
- Aluminium, stainless steel



1:1 Fast-Flo®

- Max flow: 19 lpm (5 gpm)
- UL options available



Husky Twistork Agitator

- Available with acetal or polypropylene
- Husky 515 diaphragm pump
- Mix paint, resins, urethanes, epoxies and latex materials up to 1000 cps



Priming Piston Ink Pump

- Enclosed, dual seal wet cup for longer seal life
- Runaway control with optional DataTrak™



Hydraulic Ink Pump

- Up to 3 times more efficient than pneumatic pumps
- Typical applications:
 - Letterpress inks
 - Lithographic inks



Hydra-Clean® Pressure Washers

- High pressure cleaning and sanitizing
- Air-operated and hydraulic for hazardous or confined areas
- 10:1, 12:1, 23:1, 30:1 or 45:1 ratio options
- Available in wall, cart or drum mount packages



All written and visual data contained in this document are based on the latest product information available at the time of publication. Graco reserves the right to make changes at any time without notice.

Visit us at www.graco.com/process for product information or to request a demo.

